POWER TOOLS RANGE OF CORDLESS POWER TOOLS 18V

with Li-Ion technology



COMPREHENSIVENESS, POWER AND EFFICIENCY







aawlplug

POWER TOOLS RANGE OF CORDLESS POWER TOOLS

WITH LI-ION TECHNOLOGY

Strong and efficient lithium-ion Rawlplug 18V batteries.

RawlCHARGER

Fast charger 18V 6,5A

R-CHR-186501

- Our large battery capacity enables long-term operation without unnecessary downtime.
- Lithium-ion technology allows you to fast charge the battery.
- Rawlplug's 18V battery is used to power all power tools in the range.
- High-quality lithium-ion cells provide long-term and effective battery operation.
- The charge level indicator allows you to properly plan your working time.



RawiHAMMER Rotary hammer SDS-PLUS 18V R-PRH18

RawlWRENCH

Impact wrench 18V R-PIW18

> RawlWRENCH Impact driver 18V R-PID18

RawlDRIVER Drill driver 18V R-PDD18

RawlDRIVER Drywall screwdriver 18V R-PDS18

RawlGRINDER -- Angle grinder 18V R-PAG18



NEW



RawlBATTERY

RawlBATTERY

Li-Ion battery 18V 5.0Ah

18 V 5.0 AM

R-BAT-185001



Charger 18V 1.5A R-CHR-181501

Rawlbattery LI-ION 18V R-BAT-185001 18V / 5,0 AH R-BAT-182001 18V / 2,0 AH

The RawlBattery 18V batteries are standardised and extremely efficient power sources dedicated to the Rawlplug 18V series of power tools. Thanks to their refined electronic control systems and top-quality components, they stand out among similar solutions with their exceptional performance and reliability, offering long working times and trouble-free operation of power tools.





Designed for powering all cordless power tools of the Rawlplug 18V series

TECHNICAL PARAMETERS

Index	R-BAT185001
Battery voltage	18 V
Battery capacity	5,0 Ah
Power	90 Wh
Charge level indicator	YES

001	Index	R-BAT182001
	Battery voltage	18 V
	Battery capacity	2,0 Ah
	Power	36 Wh
	Charge level indicator	YES

OFFER 🗸

Battery LI-ION 18V, 5,0Ah **R-BAT-185001**

Battery LI-ION 18V, 2,0Ah **R-BAT-182001**





RELATED PRODUCTS 🗸



Rawlhammer R-PRH18-XL2 ROTARY HAMMER SDS-PLUS 18V

Efficient electropneumatic impact

mechanism generating an energy of 2.0 J with a frequency of up to 4400 bpm allows for extremely effective drilling of holes up to 20 mm in diameter in concrete.

10 18V | 5.0 At

4 functions - drilling / hammer drilling / chiseling / positioning the chisel makes the rotary hammer an extremely versatile power tool

The SDS-plus tool shank ensures full compatibility with a wide range of accessories available on the market and enables effective transfer of impact energy

Ergonomic mode selector allows convenient and quick switching between power tool function

LED illuminates the workplace to increase user's comfort and safety

 The RawlCase system allows easy and convenient storage of the power tool with all accessories and the possibility of connecting with additional cases for easy transport





Rubberised, profiled handle increases grip and user ergonomics

Compact design and lightweight construction reduces fatigue during long-term use

Two Li-Ion batteries with 5.0 Ah capacity and a 50 minute fast charger is included with the set to guarantee uninterrupted work



18V 5.0 At

APPLICATIONS 🗸

Drilling holes in concrete up to Ø 20 mm	
Drilling holes in wood up to Ø 22 mm	
Drilling holes in metal up to Ø 13 mm	
Façades and roofs thermal insulations	



TECHNICAL PARAMETERS

Index	R-PRH18-XL2	Impact frequency	0 - 4400 bpm
Battery voltage	18 V	Rotational speed	0 - 1200 rpm
Battery capacity	5.0 Ah	Maximum drilling capacity:	
Number of batteries included	2	concrete	20 mm
Charging time	50 min	wood	22 mm
Tool holder	SDS - plus	metal	13 mm
Impact energy	2.0 J		

EQUIPMENT 🗸



Concrete Screw Anchor R-LX-HF	Stainless steel throughbolt R-HPTII-A4	Universal nylon plug 4ALL	Nylon Frame Fixings long expansion zone R-FF1-L
Drill bits Rebardrill SDS-plus RT-SDSR	Drill bits Aggressor SDS-plus RT-SDSA	Drill bits Brickdrill SDS-plus RT-SDSB	Hollow drill bits Dustlessdrill SDS-plus RT-SDSH
2000000	MARTIN .	100000	

18V | 5.0 Ah

Rawlwrench R-PIW18-XL2 IMPACT WRENCH 18V



The RawlCase system allows easy and convenient storage of the power tool with all accessories and the possibility of connecting with additional cases for easy transport

Ergonomically positioned left / right rotation switch allows a convenient and quick change between screwing and unscrewing

Electronic protection **stop system** engages during jamming to protect the user and the power tool





APPLICATIONS V

Installation of R-LX screws Ø 8-14mm

Timber constructions: screwing screwsup to Ø 24 mm Metal constructions: assembly of metric screws

(up to M24)



TECHNICAL PARAMETERS

Index	R-PIW18-XL2	Tool holder	1/2"
Battery voltage	18 V	Rotational speed	0 - 1900 rpm
Battery capacity	5.0 Ah	Impact frequenc	0 -2800 bpm
Number of batteries included	2	Maximum bolt size	M24
Charging time	50 min		
Maximum torque	1000 Nm		

EQUIPMENT 🗸





RawlWRENCH R-PID18-XL2 IMPACT DRIVER 18V

Drilling mode enables efficient use in timber and wood-based materials

Compact design and lightweight construction reduces fatigue during long-term use

LED illuminates the workplace to increase user comfort and safety

Electronic adjustable torque range to match power tool parameters for specific applications

Two Li-Ion batteries with 5.0 Ah capacity and a 50 minute fast charger are included with the set to guarantee uninterrupted work

Auto Stop Control ASC, torque cut off mode prevents damage to the material surface during screwing

10 18V 5.0

Powerful brushless motor ensures high efficiency of the mechanism and increases the life time of the tool

Rubberised, profiled handle increases grip and user ergonomics

Multihead tool holder - 1/4" hexagonal shank for bits and 1/2" square for sockets provides broad usability of the power tool

> **Hook** for suspending the screwdriver on the belt, which facilitates work in places where it is not possible to put the tool down

The RawlCase system allows easy and convenient storage of the power tool with all accessories and the possibility of connecting with additional cases for easy transport



APPLICATIONS V

Timber constructions: Screwing screws up to Ø 14 mm
Metal constructions: Assembly of metric screws (up to M14)
Installation of R-LX concrete screws up to Ø 8 mm
Frame pins and others up to Ø 14 mm (e.g. FF1, 4ALL)
Sheet metal drilling up to Ø 10 mm x 2 mm thick
Wooden constructions: Drilling in wood or chipboard (up to Ø 30 mm)

TECHNICAL PARAMETERS



Index	R-PID18-XL2	Tool holder	1/4" HEX / 1/2"
Battery voltage	18 V	Rotational speed	0 - 1100 / 2600 /
Battery capacity	5.0 Ah		3200 rpm
Number of batteries included	2	Impact frequency	0 -1200 / 2700 / 3800 bpm
Charging time	50 min	Maximum bolt size	M14
Maximum torque	210 Nm		

EQUIPMENT 🗸





I[©]RAWLPLUG[®]

RawLDRIVER R-PDD18-XL2 DRILL DRIVER 18V

16 + 1 positions of the clutch allows optimal selection of torque for driving of bolts and screws of different sizes depending on the type of substrate

Compact design and lightweight construction reduces fatigue during long-term use

The LED illuminates the workplace to increase the user comfort and safety

Ergonomically positioned left / right rotation switch allows a convenient and quick change between screwing and unscrewing

Two Li-Ion batteries

with 5.0 Ah capacity and a 50 minute fast charger are included with the set, to guarantee uninterrupted work **Two gears** allow you to adjust the speed and torque to your job

10 18V 15.0 A

Powerful brushless motor

ensures high efficiency of the mechanism which increases the life time of the power tool

Rubberised, profiled handle increases grip and user ergonomics

The single-sleeve 13 mm drill chuck makes it easy to install all accessories

> **Hook** for suspending the screwdriver on the belt, facilitates work in places where it is not possible to put thetool down



APPLICATIONS V

Timber constructions: Screwing screws up to Ø 6 mm

Metal constructions: Assembly of metric screws

(up to M6)

Frame pins and others up to Ø 14 mm (e.g. FF1, 4ALL)

Drilling in sheet metal with a thickness of 2 mm to Ø 10mm

Wooden constructions: Drilling in wood or chipboard (up to Ø 32 mm) or chipboard (up to Ø 32 mm)

TECHNICAL PARAMETERS





Index	R-PDD18-XL2	Number of clutch settings	16 + 1
Battery voltage	18 V	Chuck	1.5 - 13 mm
Battery capacity	5.0 Ah	Rotational speed 1st gear	0 - 550 rpm
Number of batteries included	2	Rotational speed 2nd gear	0 - 2000 bpm
Charging time	50 min	Maximum drilling diameter in wood	Ø 36 mm
Maximum torque	60 Nm	Maximum drilling diameter in metal	Ø 13 mm

EQUIPMENT 🗸



RELATED PRODUCTS 🗸



The RawlCase system allows easy and convenient storage of the power tool with all accessories and the possibility of connecting with additional cases for easy transport



Rawldriver R-PDS18-M2A DRYWALL SCREWDRIVER 18V





Timber profiles: Driving screws up to Ø 4.2mm




TECHNICAL PARAMETERS 🗸

Index	R-PDS18-M2A	Tool holder	1/4" HEX
Battery voltage	18 V	Rotational speed	5000 rpm
Battery capacity	2.0 Ah	Maximum screws diameter	2.5 - 4.2 mm
Number of batteries included	2	Maximum screws length	20 - 57 mm
Charging time	60 min		

EQUIPMENT 🗸



Operating instructions



RawLGRINDER R-PAG18-XL2 ANGLE GRINDER 18V



The RawlCase system allows easy and convenient storage of the power tool with all accessories and the possibility of connecting with additional cases for easy transport





APPLICATIONS V

Timber constructions: Barking/grinding wood

Grinding and cutting of stainless and carbon steels

Grinding and cutting of concrete and reinforced lintels

TECHNICAL PARAMETERS



Index	R-PAG18-XL2	Charging time	50 min
Battery voltage	18 V	Disc diameter	125 mm
Battery capacity	5.0 Ah	Spindle diameter	22.2 mm
Number of batteries included	2	Rotational speed	8 500 rpm

EQUIPMENT V













CHARGER 18V RawlCHARGER R-CHR-186501 18V / 6,5 A R-CHR-181501 18V / 1,5 A

The charger is compatible with all power tools and batteries of the Rawlplug 18V series



Battery cooling - charger equipped in cooling system to increase the service life of battery while fast process charging

Fast charging reduces downtime during operation

Universality - charger compatible with all power tools and batteries from the Rawlplug 18V series





Charging current 1.5 A - charging parameters selected for speed process and increase battery lifetime



Designed for use with all 18V Rawlplug batteries

TECHNICAL PARAMETERS

Index	R-CHR-186501	Index	R-CHR-181501
Charging voltage	18 V	Charging voltage	18 V
Charging Current	6,5 A	Charging Current	1,5A
Charging time battery 5,0 Ah	50 min	Charging time battery 2,0 Ah	60 min

OFFER 🗸

Charger **R-CHR-186501**

Charger R-CHR-181501





I[©]RAWLPLUG®

UNITED KINGDOM

 Rawlplug Ltd

 Skibo Drive

 Thornliebank Industrial Estate

 Glasgow C46 8JR

 Tel: + 44 (0) 141 638 7961

 Fax: + 44 (0) 141 638 7397

 Email: rawlbech@rawlplug.co.uk

 Web: www.rawlplug.com

1-10

SWEDEN

Rawl Scandinavia AB Baumansgatan 4 593 32 Västervik Tel: + 46 (0) 4903 0660 Email: info@rawlplug.se Web: www.rawlplug.se

CZECH REPUBLIC

Koelner CZ s.r.o Palackého 1154/76A 702 00 Ostrava-Přívoz Tel: + 420 596 636A 397 Email: objednavky@rawlplug.cz Web: www.koelner.cz Web: www.rawlplug.cz

LITHUANIA

UAB Koelner Vilnius Žarijų g. 2 LT-02300, Vilnius Tel: + 370 (5) 2324 862 Email: koelner@koelner.lt Web: www.koelner.lt

CHINA

Rawlplug Shanghai Trading Co., Ltd.

Unit 801, 233, Rushan Road Shanghai, P.R. China Tel:+86 189 1882 8527 Email: henry.yang@rawlplug.com www.rawlplug.com

IRELAND

15

Rawlplug Ireland Ltd Unit 10 Donore Business Park Donore Road Drogheda Co Louth A92 C522 Teit + 353 (0) 41 9844 338 Email: sales@rawlplug.ie Web: www.rawlplug.ie

POLAND Rawlplug S.A.

ul. Kwidzyńska 6C, 51-416 Wrocław Tel: +48 (71) 3260 100 Tel: +48 (71) 37 26 111 Email: info@koelnerpolska.pl Web: www.rawlplug.com

SLOVAKIA

Koelner Slovakia s.r.o. Dlhá 95 010 09 Žilina Tel: + 421 415 003 900 Emaii: objednavky@rawlplug.sk Web: www.roawlplug.sk

UNITED STATES OF AMERICA

Rawlplug Inc. 225 West Washington Ste 2600 Chicago IL 60605 Tel.: + 1 302 658 7581 www.rawlplug.us

ITALY Rawlplug Italia srl Via Savonarola 217 Padova cap 35137

Padova cap 35137 Tel.: +39335287639 www.rawlplug.it

FRANCE

RAWLPLUG France Bâtiment DC6, ZAC de la Feuchère 16, rue Jean Mermoz 77290 Compans Tel: + 33 (0) 1 6021 5020 Email: rawl@rawl.fr Web: www.rawlplug.fr

HUNGARY

Koelner Hungária Kft Jedlik Ányos út. 34 2330 Dunaharaszti Tel: + 36 (24) 520 400 Email: info@koelner.hu Web: www.koelner.hu

RUSSIA Koelner Trading KLD LLC

ul. Dzerzhinskogo 219 236034 Kaliningrad Tel: + 7 (4012)65 85 75 Email: info@koelner-trading.ru Web: www.koelner-trading.ru

INDIA

Rawl India Services Private Limited Prestige Meridian-1, M.G. Road, Sector-29, Bangalore, Karnataka India, 560001 Tel: +91 9650495828 Email: Info@rawlplugindia.com Web: rawlplug.com

THAILAND Rawlplug Manufacturing

(Thailand) Limited Address: 888/43 Moo 9 T.Bangpla, A.Bangplee Samutprakarn 10540 Thailand Tel.: +662 731 4788 www.tmaxcorp.co.th/

UNITED ARAB EMIRATES

Rawlplug Middle East FZE P.O. Box 261024 Dubai, UAE Warehouse No. RA08BC01 Tel: + 971 (4) 8839 501 Email: dubai@rawlplug.co.uk Web: www.rawl.ae

GERMANY

Koelner Deutschland GmbH Gmünder Str. 65 73614 Schorndorf Tel: +49 (0) 7181 977 72-0 Email: info@koelner-befestigung.de Web: www.rawlplug.com

UKRAINE Koelner Ukraine LLC

Lvivska Bichna, 6 Sokilnyky Pustomyty Dstr., Lviv Reg. 81130 Tel: + 380 (32) 2440 744 Email: koeiner@koeiner.ua Web: www.koeiner.ua

SINGAPORE

Rawlplug Singapore Pte. Ltd. Blk 302, #04-11, 258 Loyang Crescent Loyang Offshore Supply Base Singapore 506817 Tel: + 65 9078 5220 Email: jacek.nowicki@rawlplug.com.sg Web: www.rawlplug.com



SERVICE: www.rawlplug.com